

Flanged Type 'F' / Model 6 / Pressure Gauge



Note: Gauge head is screwed into flange.

Part Numbers

Pressure Range	Standard Service	Corrosive Fluid Service
10,000 psi	61111	61131
15,000 psi	61211	61231
20,000 psi	61411	61431
70,000 kPa	62111	62531
100,000 kPa	62211	62631
140,000 kPa	62411	62731
70 Bar	63111	63131
1,040 Bar	63611	63631
1,400 Bar	63711	63731

Also available in kg/cm²

★ We carry other flanged style gauges as well.

Shipping Weights: a) 1 7/16 API 6BX 29 lbs (13.2 kg)
b) 2 1/16 API 6BX 29 lbs (13.2 kg)

Heavy Duty Type 'F' / Model 6 / Pressure Gauge

with 2" or 3" 1502 NUT CONNECTION



Calibration:

All gauges are calibrated to within 1% tolerance.

GAUGE DESCRIPTION	NUT DESCRIPT.	PART NUMBER	SHIP WT.
0-6000 PSI std serv	2"1502-15M	NF 106-N2-15	30 #
0-6000 PSI H2S serv	2"1502-10M	NF 306-N2-10	30 #
0-10000 PSI std serv	2"1502-15M	NF 110-N2-15	30 #
0-10000 PSI H2S serv	2"1502-10M	NF 310-N2-10	30 #
0-15000 PSI std serv	2"1502-15M	NF 115-N2-15	30 #
0-15000 PSI Red Line serv	2"1502-10M	NF 315-N2-10	30 #
0-6000 PSI std serv	3"1502-15M	NF 106-N3-15	40 #
0-6000 PSI H2S serv	3"1502-10M	NF 306-N3-10	40 #
0-10000 PSI std serv	3"1502-15M	NF 110-N3-15	40 #
0-10000 PSI H2S serv	3"1502-10M	NF 310-N3-10	40 #
0-15000 PSI std serv	3"1502-15M	NF 115-N3-15	40 #
0-15000 PSI Red Line H2S	3"1502-10M	NF 315-N3-10	40 #

To place an order, please specify:

- 1 Unit of measure and pressure range.
- 2 Type of service.
- 3 O'Drill part number.